

# MATERIAL SAFETY DATA SHEET

## 1. American Polywater Corporation

11222 - 60th Street North  
P.O. Box 53  
Stillwater, MN 55082 USA  
Phone: 1-651-430-2270  
Fax: 1-651-430-3634

**Emergency Number:** 1-651-430-2270

**Product Name: Klein Polymer  
Wire Pulling Lubricant  
1 51015, 51017, 51018**

**Chemical Description:** Low Solids Water Solution  
**Canada WHMIS Class:** NC

**Date Reviewed:** April 26, 2006

**Reviewed By:** S. H. Dahlke

## 2. HAZARDOUS INGREDIENTS

This product contains no reportable hazardous components under 29 CFR 1910.1200. There are no OSHA or ACGIH threshold limit values for the product or any of its ingredients.

All components are listed on the TSCA inventory.

## 3. HAZARDS IDENTIFICATION

	<u>HMIS</u>	<u>NFPA</u>	<u>Key</u>	
Health	0	0	0-minimal	3-serious
Flammability	0	0	1-slight	4-severe
Reactivity	0	0	2-moderate	

## 4. FIRST AID

**Eye Contact:** Flush eyes with a large quantity of water for 15 minutes. If irritation continues, seek medical attention.

**Skin Contact:** If skin becomes irritated, wash area thoroughly with soap and water. If irritation continues, seek medical attention.

**Inhalation (Breathing):** No first aid expected to be required. Not an inhalation hazard.

**Ingestion (Swallowing):** No first aid expected to be required. If difficulties arise, contact a physician.

## 5. FIRE AND EXPLOSION HAZARD

**Flash Point:** No flash via TCC.

**Flammable Limits:** Product is not flammable.

**Extinguishing Media:** Does not apply.

**Special Procedures:** Does not apply.

**Unusual Hazards:** Sealed container can build up pressure when exposed to high heat. Cool containers with water.

**Hazardous Decomposition Products:** High temperature steam, potentially carbon monoxide and carbon dioxide.

## 6. ACCIDENTAL RELEASE MEASURES

Klein Polymer Lubricant is extremely slippery. It should be washed, swept, or squeegeed from floor using wet mops. Oxidizing agents, such as household bleach, can be used to eliminate the slippery character. Outside, spills should be covered with sand, dirt, gravel or calcium chloride.

## 7. HANDLING AND STORAGE

Keep product containers closed when not in use. Avoid spills and clean them up immediately when they occur. Product is very slippery.

**8. CONTROL MEASURES**

**Respiratory Protection:** Normal ventilation adequate.

**Protective Gloves:** For repeated or prolonged skin contact of sensitive individuals, impermeable gloves are recommended to prevent possible irritation.

**Eye Protection:** Safety glasses recommended.

**9. PHYSICAL DATA**

**Appearance:** Opaque, light-blue viscous gel with no odor.

**Vapor Pressure:** 18mm @ 72°F

**Specific Gravity (H<sub>2</sub>O = 1):** 1.01

**Percent Volatiles (Weight):** 97%

**Viscosity:** 70,000-110,000 cps. @ 10 rpm.

**Boiling Point:** 212°F (100°C)

**Ignition Temperature:** None

**Vapor Density (Air = 1):** .9 to 1.1

**Solubility in Water:** Infinite

**Percent Water (Weight):** 97%

**pH:** 6.5 to 8.5

**10. REACTIVITY DATA**

**Stability:** Stable

**Incompatibility:** Avoid materials which react with water.

**Hazardous Polymerization:** Will not occur.

**11. HEALTH HAZARD/TOXICOLOGICAL INFORMATION**

**Eye Contact:** Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

**Skin Contact:** This product has low skin irritation potential. There is no dermal toxicity hazard.

**Inhalation (Breathing):** No inhalation hazard expected with water vapor.

**Ingestion (Swallowing):** Based on ingredients, LD<sub>50</sub> (rat) is estimated to be well over 50 g/kg.

**Carcinogenic Status:** This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC or OSHA, nor have any of its components.

**12. DISPOSAL CONSIDERATIONS**

Dispose of product in accordance with local, county, state, and federal regulations. Klein Polymer Lubricant is not considered hazardous waste under RCRA.

**13. TRANSPORTATION**

**DOT Hazard Class:** Not Applicable

**DOT Shipping Name:** Not Applicable

For domestic purposes, this product is not defined or designated as a hazardous material by the U.S. Department of Transportation.

**14. REGULATORY STATUS**

**Hazard Categories for SARA Section 311/312 Reporting**

**Acute**  
No

**Chronic**  
No

**Fire**  
No

**Pressure**  
No

**Reactive**  
No

Components

CERCLA/SARA Sec. 302 Hazardous Substance RQ      EHS TPQ

SARA Sec. 313 Toxic Release

The components of Klein Polymer Lubricant are not affected by these Superfund regulations.