

# MATERIAL SAFETY DATA SHEET

## 1. American Polywater Corporation

11222 - 60th Street North  
P.O. Box 53  
Stillwater, MN 55082 USA  
Phone: 1-651-430-2270  
Fax: 1-651-430-3634

**Product Name: Klein Polymer  
Wire Pulling Lubricant  
(51015, 51017, 51018)**

**Date Reviewed:** August 11, 2009

**Reviewed By:** S. H. Dahlke

**Emergency Number:** 1-651-430-2270

## 2. HAZARDOUS INGREDIENTS

This product contains no reportable hazardous components under 29 CFR 1910.1200. There are no OSHA or ACGIH threshold limit values for the product or any of its ingredients.

All components are listed on the TSCA inventory.

## 3. HAZARDS IDENTIFICATION

### \*\*\*Emergency Overview\*\*\*

Low Solids, waterbased lubricant. Thick blue gel. Propylene glycol added as a winterizing agent.

Lubricant is electrically conductive when applied. Dry from conductor before energizing circuit. In case of eye contact, flush eyes with water. Industrial use only. Very slippery if spilled.

**Eye Contact:** Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

**Skin Contact:** This product has low skin irritation potential. There is no dermal toxicity hazard.

**Inhalation (Breathing):** No inhalation hazard expected with water vapor.

**Ingestion (Swallowing):** This product has low ingestion hazard.

**Carcinogenic Status:** This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC or OSHA, nor have any of its components.

## 4. FIRST AID

**Eye Contact:** Flush eyes with a large quantity of water for 15 minutes. If irritation continues, seek medical attention.

**Skin Contact:** If skin becomes irritated, wash area thoroughly with soap and water. If irritation continues, seek medical attention.

**Inhalation (Breathing):** No first aid expected to be required. Not an inhalation hazard.

**Ingestion (Swallowing):** No first aid expected to be required. If difficulties arise, contact a physician.

## 5. FIRE AND EXPLOSION HAZARD

**Flash Point:** No flash via TCC.

**Flammable Limits:** Product is not flammable.

**Extinguishing Media:** Does not apply.

**Special Procedures:** Does not apply.

**Unusual Hazards:** Sealed container can build up pressure when exposed to high heat. Cool containers with water.

**Hazardous Decomposition Products:** High temperature steam, potentially carbon monoxide and carbon dioxide.

## 6. ACCIDENTAL RELEASE MEASURES

Klein Polymer Lubricant is extremely slippery. It should be washed, swept, or squeegeed from floor using wet mops. Oxidizing agents, such as household bleach, can be used to eliminate the slippery character. Outside, spills should be covered with sand, dirt, gravel or calcium chloride.

## 7. HANDLING AND STORAGE

Keep product containers closed when not in use. Avoid spills and clean them up immediately when they occur. Product is very slippery.

**8. CONTROL MEASURES**

**Respiratory Protection:** Normal ventilation adequate.

**Protective Gloves:** For repeated or prolonged skin contact of sensitive individuals, impermeable gloves are recommended to prevent possible irritation.

**Eye Protection:** Safety glasses recommended.

**9. PHYSICAL DATA**

**Appearance:** Opaque, light-blue viscous gel with no odor.

**Vapor Pressure:** 18mm @ 72°F

**Specific Gravity (H<sub>2</sub>O = 1):** 1.01

**Percent Volatiles (Weight):** 97%

**Viscosity:** 70,000-110,000 cps. @ 10 rpm.

**VOC Content:** 200 gms/L

**Boiling Point:** 212°F (100°C)

**Ignition Temperature:** None

**Vapor Density (Air = 1):** .9 to 1.1

**Solubility in Water:** Infinite

**Percent Water (Weight):** 97%

**pH:** 6.5 to 8.5

**10. REACTIVITY DATA**

**Stability:** Stable

**Incompatibility:** Avoid materials which react with water.

**Hazardous Polymerization:** Will not occur.

**11. HEALTH HAZARD/TOXICOLOGICAL INFORMATION**

Refer to Section 3 for available information on potential health effects.

Based on ingredients, LD<sub>50</sub> (rat) is estimated to be well over 50 g/kg.

**12. DISPOSAL CONSIDERATIONS**

Dispose of product in accordance with local, county, state, and federal regulations. Klein Polymer Lubricant is not considered hazardous waste under RCRA.

**13. TRANSPORTATION**

**DOT Hazard Class:** Not Applicable

**DOT Shipping Name:** Not Applicable

For domestic purposes, this product is not defined or designated as a hazardous material by the U.S. Department of Transportation.

**14. REGULATORY STATUS**

**Canada WHMIS Class:** NC

**Hazard Categories for SARA  
Section 311/312 Reporting**

**Acute**  
No

**Chronic**  
No

**Fire**  
No

**Pressure**  
No

**Reactive**  
No

**Components**

**CERCLA/SARA Sec. 302  
Hazardous Substance RQ EHS TPQ**

**SARA Sec. 313  
Toxic Release**

The components of Klein Polymer Lubricant are not affected by these Superfund regulations.