

Fall-Arrest/Suspension Harnesses

Features:

Friction-style buckles for adjustments over a continuous range of sizes.

Suspension D-rings. Drop-forged circle D-rings have corrosion-resistant finish, wear-minimizing rollers, and are proof-loaded to meet OSHA regulations.

Fall-arrest D-ring with roller.

Drop-forged circle D-ring has corrosion-resistant finish, wear-minimizing roller and is proof-loaded to meet OSHA regulations. Easily adjusts for proper fit and function.

Seat strap adds extra comfort in normal use as well as support after a fall.



Fall-arrest/suspension harnesses are designed to arrest free falls and distribute impact forces as required by OSHA.

Identity and warning tags and/or labels (not shown) are reminders of proper application and inspection procedures. The Klein name, model, date of manufacture, and OPE-system application symbol(s) are permanently and clearly inscribed on these tags and labels.

Harnesses are certified and compliant with ANSI and CSA requirements.

When using any Klein harness, always follow the A-B-C rule. See pages 6 to 11 for details.



Sizing Table

Use your waist size to determine the correct ordering size.

Waist Size Range	Size
32" to 40" (813 – 1016 mm)	Small
36" to 44" (914 – 1118 mm)	Medium
40" to 48" (1016 – 1219 mm)	Large
44" to 52" (1118 – 1321 mm)	Extra Large
48" to 56" (1219 – 1422 mm)	2X Large



Fall-Arrest/Suspension Harnesses

Fall-Arrest/Suspension Harness

Additional Features:

- Harness comes with 5' (1.5 m) long, 1/2" (13 mm) diameter nylon filament V-sling with locking snap-hooks for suspension.
- V-sling design places worker in upright position when held taut. V-sling is for suspension purposes only and is NOT to be used for fall-arrest.
- Durable 1-3/4" (44 mm) Type 13, or equivalent, nylon webbing harness construction.
- Waist and shoulder straps have friction-style buckles for adjustments over a continuous range of sizes.



Cat. No.	Size Description	Shipping Weight (lbs.)
87012	Medium	7.9



Specialty Harnesses


Fall-Arrest/Positioning/Retrieval Harness

Features:

- Permanently attached waist belt can conveniently hold tunnel-loop pouches/holders.
- Waist belt is permanently attached to harness on one end and inserts through 5" (127 mm) backstrap loops for a wide range of sizes and increased comfort from better tool weight distribution.
- Durable 1-3/4" (44 mm) Type 13, or equivalent, nylon webbing harness construction.
- Easy-connect chest and leg buckles with friction-slide adjusters for quick engagement/disengagement.
- Waist belt has tongue buckle and grommets for a comfortable fit and positive buckle connection.
- Harness is certified and compliant with ANSI and CSA requirements.



Cat. No.	Size Description	Shipping Weight (lbs.)
87850	Small	6.5
87851	Medium	6.5
87852	Large	6.6
87853	Extra Large	6.7



With Easy-Connect Hardware

