


Fall-Arrest/Positioning Harness – Tower Work

Features:

- Heavy-duty harness design is ideal for workers on transmission towers and other elevated sites.
- 5" x 17" (127 mm x 43 cm) x 1/2" (13 mm) thick, padded leather seat cushion for hours of comfort and support.
- Chest D-ring for convenient ladder climbing applications.
- Seat cushion is removable and attaches with two snap-hooks and includes two leather pads near connecting hardware for added comfort.
- Semi-floating lineman's style body belt with tool loops is built into the harness.
- Waist belt can conveniently hold slotted and tunnel-loop pouches/holders.
- Durable 1-3/4" (44 mm) Type 13, or equivalent, nylon webbing harness construction.
- Contoured shoulder pads help cushion the weight of the harness when fully loaded with equipment for improved comfort.
- Easy-connect chest and leg buckles with friction-slide adjusters for quick engagement/disengagement.
- Accessories include: glove-bag ring, two-way knife snap, and tape thong.
- Harness is certified and compliant with ANSI and CSA requirements.




With Easy-Connect Hardware

Cat. No.	Size Description	Shipping Weight (lbs.)
87962	Small	12
87963	Medium	12
87964	Large	12
87965	Extra Large	13



Seat cushion attachment close-up



Specialty Harnesses

Fall-Arrest/Suspension Harness with Bosun's Chair

Features:

- Permanently attached Bosun's chair provides an excellent workstation for prolonged suspension jobs.
- Bosun's chair has one forged circle D-ring with roller at front for attaching to a suspension-connecting device.
- 12" x 24" (30 x 61 cm) x 1" (25 mm) thick, laminated wood seat is reinforced on the underside with metal cleats.
- Web support sling crosses on the underside of the chair and is woven through four seat slots and cleats.
- Ultra-Hyde™ lined waist and leg straps. Ultra-Hyde™ is a material that looks and feels like leather, yet requires little maintenance.
- Durable 1-3/4" (44 mm) Type 19, or equivalent, nylon webbing harness construction.
- Chest and shoulder straps have friction-style buckles for adjustments over a continuous range of sizes.
- Waist and leg straps have tongue buckles and grommets for a comfortable fit and positive buckle connection.
- Harness is certified and compliant with ANSI and CSA requirements and meets OSHA standard 1910.28.



Harnesses



Cat. No.	Size Description	Shipping Weight (lbs.)
87044	Medium	13.6




Fall-Arrest/Positioning/Suspension Harness – Tree Trimming Work


Features:

- Permanently attached tree-trimmer's belt has four forged circle D-rings with rollers (two upward-facing on saddle for suspension and two forward-facing on waist belt for positioning).
- Durable 1-3/4" (44 mm) Type 13, or equivalent, nylon webbing harness construction.
- Softee™ back and seat pads are made of non-abrasive nylon for extra comfort during prolonged use.
- Easy-connect chest and leg buckles with friction-slide adjusters for quick engagement/disengagement.
- An optional V-sling for suspension use can be added by ordering Cat. No. 87420.
- Harness is certified and compliant with ANSI and CSA requirements.


Cat. No.	Size Description	Shipping Weight (lbs.)	CSA®
87890	Small	8.3	
87891	Medium	8.2	
87892	Large	8.6	
87893	Extra Large	8.5	




Seat strap allows worker to lean back.



Seat strap allows for semi-sitting position.



In full sitting position, worker can be lifted or lowered as needed.



With Easy-Connect Hardware

